

* 1 Identification

- **Product identifier**
- **Trade name:** 77424 2.1 VOC High Solids DTM Primer/Sealer - Black
- **Article number:** 77424
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
High Teck Products
PO Box 24631, West Palm Beach, FL 33416
- **Information department:**
877-900-8325
info@highteckproducts.com
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Talc
acetone
Carbon black
ACETOACETATE RESIN

· **Hazard statements**

H225 *Highly flammable liquid and vapor.*
H315 *Causes skin irritation.*
H319 *Causes serious eye irritation.*
H317 *May cause an allergic skin reaction.*
H351 *Suspected of causing cancer.*
H335 *May cause respiratory irritation.*

· **Precautionary statements**

P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*
P261 *Avoid breathing dust/fume/gas/mist/vapors/spray*
P280 *Wear protective gloves / eye protection / face protection.*
P240 *Ground/bond container and receiving equipment.*
P303+P361+P353 *IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P321 *Specific treatment (see on this label).*
P304+P340 *IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*
P312 *Call a poison center/doctor if you feel unwell.*
P363 *Wash contaminated clothing before reuse.*
P405 *Store locked up.*
P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
P403+P235 *Store in a well-ventilated place. Keep cool.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



(Contd. on page 3)
USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1
FIRE	3
REACTIVITY	0

Health = 1
Fire = 3
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

*** 3 Composition/information on ingredients**

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

7727-43-7 barium sulphate, natural	13 - 30%
67-64-1 acetone	13 - 30%
ACETOACETATE RESIN	13 - 30%
14807-96-6 Talc	13 - 30%
110-43-0 heptan-2-one	7 - 10%
EPOXY RESIN	1.5 - 5%
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	1.5 - 5%
25036-25-3 EPOXY RESIN	1.5 - 5%
1314-13-2 zinc oxide	1.5 - 5%
1333-86-4 Carbon black	1-1.5%
71-36-3 butan-1-ol	1-1.5%
1330-20-7 xylene	1-1.5%
Fluorosurfactant	≤1%

*** 4 First-aid measures**

· **Description of first aid measures**

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 3)

* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)
USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7727-43-7 barium sulphate, natural

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 5* mg/m³
*inhalable fraction; E

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
BEI

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³

REL Long-term value: 3.5* mg/m³
*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³
*inhalable fraction

71-36-3 butan-1-ol

PEL Long-term value: 300 mg/m³, 100 ppm

REL Ceiling limit value: 150 mg/m³, 50 ppm
Skin

TLV Long-term value: 61 mg/m³, 20 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

· **Ingredients with biological limit values:**

67-64-1 acetone

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 6)

USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 5)

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

(Contd. on page 7)
USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 6)

· Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C
· Flash point:	-18 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	465 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	2.6 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C:	233 hPa
· Density at 20 °C:	2.13236 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	31.5 %
VOC content:	10.7 %
	209.9 g/l / 1.75 lb/gl
Solids content:	68.6 %
· Other information	No further relevant information available.

*10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 8)
USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 7)

- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14807-96-6 Talc

2B

1333-86-4 Carbon black

2B

1330-20-7 xylene

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

*12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 8)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

*14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 Paint, special provision 640D
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**



- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** II
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Flammable liquids
- **EMS Number:** F-E,S-E
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

(Contd. on page 10)
USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 9)

- **ADR**
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":** UN1263, Paint, special provision 640D, 3, II

*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**
7727-43-7 barium sulphate, natural
14807-96-6 Talc
1314-13-2 zinc oxide
71-36-3 butan-1-ol
1330-20-7 xylene
- **TSCA (Toxic Substances Control Act):**
7727-43-7 barium sulphate, natural
67-64-1 acetone
14807-96-6 Talc
110-43-0 heptan-2-one
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene
25036-25-3 EPOXY RESIN
1314-13-2 zinc oxide
1333-86-4 Carbon black
71-36-3 butan-1-ol
1330-20-7 xylene
- **Proposition 65**
- **Chemicals known to cause cancer:**
25036-25-3 EPOXY RESIN
1333-86-4 Carbon black
1330-20-7 xylene
- **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.
- **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

(Contd. on page 11)

USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 10)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

67-64-1 acetone

I

1314-13-2 zinc oxide

D, I, II

71-36-3 butan-1-ol

D

1330-20-7 xylene

I

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone

A4

14807-96-6 Talc

A4

1333-86-4 Carbon black

A4

1330-20-7 xylene

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4 Carbon black

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02



GHS07



GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Talc

acetone

Carbon black

ACETOACETATE RESIN

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 12)

USA

Trade name: 77424 2.1 VOC High Solids DTM Primer/Sealer - Black

(Contd. of page 11)

- P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P321 *Specific treatment (see on this label).*
- P304+P340 *IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*
- P312 *Call a poison center/doctor if you feel unwell.*
- P363 *Wash contaminated clothing before reuse.*
- P405 *Store locked up.*
- P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
- P403+P235 *Store in a well-ventilated place. Keep cool.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** 877 900 8325

· **Date of preparation / last revision** 08/31/2015 / 9

· **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· * **Data compared to the previous version altered.**