




## 1 Identification of substance

- **Product details**
- **Trade name:** 39482 Flexible Polyester Glaze (w/HRDNR)
- **Article number:** 39482
- **Manufacturer/Supplier:**  
SEM Products Inc.  
651 Michael Wylie Dr.  
Charlotte, NC 28217  
(704)522-1006
- **Information department:**  
labsupport@sem.ws : SEM Products 651 Michael Wylie Dr. Charlotte, NC 28217 : phone 1-704-522-1006, M - TH 7am - 4pm EDT
- **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

## 2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	Warning:  3.2/2, 3.3/2A, 3.8/3	40 - 60%
100-42-5	styrene	Warning:  2.6/3;  3.1.1/4, 3.2/2, 3.3/2A	13 - 30%

## 3 Hazards identification

- **Hazard description:**



Harmful  
Extremely flammable

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

Extremely flammable.

Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **NFPA ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 2  
Fire = 3  
Reactivity = 0

(Contd. on page 2)

Trade name: 39482 Flexible Polyester Glaze (w/HRDNR)

(Contd. of page 1)

· **GHS label elements**



**Danger**

2.6/1 - Extremely flammable liquid and vapour.



**Warning**

3.1/4 - Harmful if inhaled.

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause respiratory irritation.

· **Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

· **Response:**

**IF ON SKIN:** Wash with plenty of soap and water.

**IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

**IF INHALED:** Remove to fresh air and keep at rest in a position comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a **POISON CENTER** or doctor/physician if you feel unwell.

Specific treatment (see label).

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

· **Storage:**

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

· **Disposal:**

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

**Trade name: 39482 Flexible Polyester Glaze (w/HRDNR)**

(Contd. of page 2)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

### 5 Fire fighting measures

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**  
Do not allow product to reach sewage system or any water course.  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.
- **Measures for cleaning/collecting:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

### 7 Handling and storage

- **Handling:**
- **Information for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Do not gas tight seal receptacle.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

### 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

**Trade name: 39482 Flexible Polyester Glaze (w/HRDNR)**

(Contd. of page 3)

**· Components with limit values that require monitoring at the workplace:**

**100-42-5 styrene**

PEL	Short-term value: C 200; 600* ppm Long-term value: 100 ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m <sup>3</sup> , 100 ppm Long-term value: 215 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 170 mg/m <sup>3</sup> , 40 ppm Long-term value: 85 mg/m <sup>3</sup> , 20 ppm
BEI	

**· Additional information:** The lists that were valid during the creation were used as basis.

**· Personal protective equipment:**

**· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**· Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

**· General Information**

<b>Form:</b>	Liquid
<b>Color:</b>	According to product specification

(Contd. on page 5)



**Trade name: 39482 Flexible Polyester Glaze (w/HRDNR)**

(Contd. of page 4)

<b>Odor:</b>	Characteristic
<b>· Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	145°C (293°F)
<b>· Flash point:</b>	31°C (88°F)
<b>· Ignition temperature:</b>	480°C (896°F)
<b>· Auto igniting:</b>	Product is not selfigniting.
<b>· Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
<b>· Explosion limits:</b>	
<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	8.9 Vol %
<b>· Vapor pressure at 20°C (68°F):</b>	8 hPa (6 mm Hg)
<b>· Density at 20°C (68°F):</b>	1.62 g/cm <sup>3</sup>
<b>· Solubility in / Miscibility with Water:</b>	Fully miscible.
<b>· Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
<b>· Solids content:</b>	100.0 %

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

### 11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**100-42-5 styrene**

Oral	LD50	5000 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Trade name: 39482 Flexible Polyester Glaze (w/HRDNR)

(Contd. of page 5)

## 12 Ecological information

- **General notes:** Generally not hazardous for water

## 13 Disposal considerations

- **Product:**
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- **DOT regulations:**



- **Hazard class:** 3
- **Identification number:** UN3269
- **Packing group:** III
- **Proper shipping name (technical name):** POLYESTER RESIN KIT, mixture
- **Label:** 3

- **Land transport TDG (Canada) and ADR/RID (Europe):**



- **Hazard class:** 3 Flammable liquids
- **UN-Number:** 3269
- **Packaging group:** III
- **Label:** 3
- **Description of goods:** 3269 POLYESTER RESIN KIT, mixture

- **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 3269
- **Label:** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-D
- **Marine pollutant:** No

(Contd. on page 7)

**Trade name: 39482 Flexible Polyester Glaze (w/HRDNR)**

(Contd. of page 6)

· **Propper shipping name:** POLYESTER RESIN KIT, mixture

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3  
 · **UN/ID Number:** 3269  
 · **Label:** 3  
 · **Packaging group:** III  
 · **Propper shipping name:** POLYESTER RESIN KIT, mixture

· **UN "Model Regulation":** UN3269, POLYESTER RESIN KIT, mixture, 3, III

### 15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

100-42-5 styrene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **IARC (International Agency for Research on Cancer)**

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

3

100-42-5 styrene

2B

13463-67-7 titanium dioxide

2B

7631-86-9 silicon dioxide, chemically prepared

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 8)



**Trade name: 39482 Flexible Polyester Glaze (w/HRDNR)**

(Contd. of page 7)

· <b>TLV (Threshold Limit Value established by ACGIH)</b>		
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4
100-42-5	styrene	A4
13463-67-7	titanium dioxide	A4
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
13463-67-7	titanium dioxide	
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Harmful  
Extremely flammable

· **Hazard-determining components of labelling:**

styrene

· **Risk phrases:**

Extremely flammable.  
Harmful by inhalation.  
Irritating to eyes, respiratory system and skin.

· **Safety phrases:**

Keep out of the reach of children.  
Keep container tightly closed and in a well-ventilated place.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
If swallowed, seek medical advice immediately and show this container or label.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Steve Gaver

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent