



3834() VINYL PREP

TECHNICAL DATA SHEET

Description

3834() VINYL PREP is a high strength combination of solvents and water. **3834()** not only cleans soil, wax and grease from the surface, but also creates a slight softening of the vinyl and prepares the surface for coating with SEM's **COLOR COAT**, **SURE-COAT™** or **CLASSIC COAT™**.

Features

- Cleans soil, wax and grease from vinyl substrates
- Convenient aerosol or quart packaging
- Prepares surface for excellent topcoat adhesion

Typical Properties

Containers	38344 - quart and 38343 - 16 oz aerosol
VOC 38343	5.37 #/g1 (644.0 g/l)
VOC 38344	5.66 #/g1 (677.8 g/l)

Handling and Application

APPLICATION: **3834()** removes solvent based contaminants and should be the second step when preparing vinyl substrates for repair or refinishing.



1. Spray or apply with a sponge or cloth to vinyl surface. Wipe thoroughly with a sponge or cloth. Excessive rubbing is not necessary.
2. Rinse with water and allow to dry. Where multiple coats of wax are present, use **3834()** liberally and rinse well, repeating the process until water no longer beads on the surface.
3. Refinish according to SEM **RAP-1, Refinishing Automotive Interior and Exterior Flexible and Rigid Substrates**.

CAUTION: Do not allow **3834()** to splash or stand on any painted surface as discoloring may occur.

STORAGE:



3834() VINYL PREP should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **38343** is 3 years when stored under normal conditions while the shelf life for **38344** is unlimited.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.